



Project:	
Type:	
Description:	

YORI MONOPOINT 1.7" INDOOR - SURFACE



Yori 1.7" Monopoint (JBox mounted)

Yori 1.7" Monopoint (Surface Mounted)

DAMP			IP20	
CUT OUT	Round: Ø 1.7"			
	5/8 in Max Ceiling Thickness			
	Precision = Refractor Optics Performance = Reflector Optics			

LIGHT ENGINE

Power LED

Example:

A . . **A.FQ31A.HW12**

Mounting

- FQ JBox mounted
- FM Surface mounted

Optic Type

- 3 Precision
- 4 Performance

Wattage

- 1 4W
- 2 9W

Optics

- A Precision 8°
- B Precision 11°
- E Precision 23°
- H Precision 40°
- B Performance 8°
- E Performance 18°
- H Performance 29°

CCT

	4W/ 9W		
<u>HW</u>	2700 K	CRI >90	lm 410/725
<u>HQ</u>	3000 K	CRI >90	lm 415/730
<u>WW</u>	3000 K	CRI >80	lm 485/844
<u>WN</u>	3500 K	CRI >80	lm 507/892
<u>NN</u>	4000 K	CRI >80	lm 530/940

Finishes

- 12 Embossed Matt White
- 31 Embossed Matt Black

NOTES

1. For 3500K CCT, must consult with factory to confirm availability.
2. For custom stem length, add .Bxx to the end of the ordering code, where xx is the custom stem length in inches, from 6" to 96" (.B06 to .B96)

All lumens shown above are initial
Lumen delivered up to 435/750lm Precision
Lumen delivered up to 450/780lm Performance
Lumen maintenance: L90 B10=50,000h

Warm Dimming COB LED

Example:

A . **3** **2** **B** . **DT** **A.FM32B.DT31**

Mounting

- FQ JBox mounted
- FM Surface mounted

Optic Type

- 3 Precision

Wattage

- 2 6.5W

Optics

- B Precision 27°

CCT

- DT 1700-3000K CRI >95 lm 10-550

6.5W

Finishes

- 12 Embossed matt white
- 31 Embossed matt black

NOTES

2. For custom stem length, add .Bxx to the end of the ordering code, where xx is the custom stem length in inches, from 6" to 96" (.B06 to .B96)

All lumen shown above are initial
Lumen delivered up to 130 lm
Lumen maintenance: L80 B10=50,000h

Project:	
Type:	
Description:	

YORI MONOPOINT 1.7" INDOOR - SURFACE

DRIVER Example: **T.FMH15.0000**

F **0000**

Dimming	Driver Location	Driver Code	Plate
<u>T</u> Phase-Cut	<u>F</u> Remote Driver	4W MH15 120V, Phase-cut, dims down to 10%, powers 1 fixture at a time	<u>0000</u> No Plate
		9W & 6.5W DT MH19 120V, Phase-cut, dims down to 10%, powers 1 fixture at a time	
<u>V</u> 0-10V		4W LZ34 120/277V, 0-10V, dims down to 1%, powers 1 fixture at a time	
		4W LD49 120/277V, 0-10V, dims down to 0.1%, powers 2 fixtures at a time	
		9W & 6.5W DT LZ32 120/277V, 0-10V, dims down to 1%, powers 1 fixture at a time	
		9W & 6.5W DT LD52 120/277V, 0-10V, dims down to 0.1%, powers 2 fixtures at a time	
<u>L</u> Lutron EcoSystem		4W ML121 120/277V, Lutron EcoSystem Soft-on, Fade-to-Black, dims down to 0.1%, powers 1 fixture at a time	
		9W ML156 120/277V, Lutron EcoSystem Soft-on, Fade-to-Black, dims down to 0.1%, powers 1 fixture at a time	

NOTES
3. For emergency driver options, consult factory

Project:	
Type:	
Description:	

YORI MONOPOINT 1.7"

INDOOR - SURFACE

Technical Info

Driver:

Remote driver.

Mounting:

FQ Option: Mounts to a junction box using a 2" canopy.

FM Option: Mounts with screw in springs.

Optical features Light source features:

1 LED/3step/50,000 hrs

Beam Angles:

Precision: 8°, 11°, 23°, 27° (Warm- dim DT option), 40°

Performance: 8°, 18°, 29°

Physical features:

Material: Die-cast aluminum

Surfaces: Ceiling

Weight: 0.5 lbs

Maximum Remote Driver Distance:

60 Ft, 18Ga

80 Ft, 16Ga

100 Ft, 14 Ga

Luminaire Description:

Fixture Features: The attractive Yori cylinder is die cast aluminum

with powder coat finish. Quickly changes beam spreads through

the use of Precision refractors or Performance reflectors and various accessories.

Fixture Benefits: Part of the Yori family of lights assures consistent design. 350° horizontal and 90° vertical aiming.

Max Fixture Total Wattage:

4W LED: 5W

9W LED: 10W

Accessories: Precision and Performance accessories available.

Warranty: 5 Year LED.

ETL listed, Union assembled


Reggiani reserves the right to change details at any time without notice.

Rev 8/10/2021


Technical Drawings

LIGHT ENGINE

Surface Mounted



JBox Mounted




Note:

Standard X stem length is 0.4". For custom stem length, add .Bxx to the end of the ordering code, where xx is the custom stem length in inches, from 6" to 96" (.B06 to .B96)


DRIVER

Medium Remote Box



FOR USE WITH: MH15, MH19, ML121, and ML156

Large Remote Box



FOR USE WITH: LZ34, LD49, LZ32, and LD52

1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.

2. Requires 3" clearance from any insulation

1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.

















2. Requires 3" clearance from any insulation

Project:	
Type:	
Description:	

YORI MONOPOINT 1.7"

INDOOR - SURFACE

ACCESSORIES PRECISION


	Description: Glass filter 1 mm	Code: 0.26400.00__	Finishes: 4A RED 5A Green 6A Blue 7A Pink 8A Yellow 9A orange
	Description: Colored Gel Slides (2 pieces)	Code: 0.26408.0000	
	Description: Selective filter 3000K - 2700K	Code: 0.26557.0000	
	Description: Selective filter 2700K - 2500K	Code: 0.26416.0000	
	Description: Selective filter 2700K - 2200K	Code: 0.26424.0000	
	Description: Selective filter 2700K - 2000K	Code: 0.26432.0000	
	Description: Selective filter 3000K - 3600K	Code: 0.26565.0000	
	Description: Selective filter 3000K - 4000K	Code: 0.26573.0000	
	Description: Dense texture honeycomb louvre	Code: 0.26440.0000	
	Description: Wide texture honeycomb louvre	Code: 0.26448.0000	
	Description: Elliptical beam lens	Code: 0.26456.0000	
	Description: Opal lens	Code: 0.26460.0000	
	Description: Spread lens	Code: 0.26468.0000	
	Description: Cross blade louvre	Code: 0.26476.0000	
	Description: Barn doors	Code: 0.26484.0000	
	Description: Cone 45 ° wall washer	Code: 0.26488.00__	Finishes: 12 White 31 Black

Project:	
Type:	
Description:	

YORI MONOPOINT 1.7"

INDOOR - SURFACE

ACCESSORIES PERFORMANCE

	Description: Glass filter 1 mm	Code: 0.26401.00__	Finishes: 4A RED 5A Green 6A Blue 7A Pink 8A Yellow 9A orange
	Description: Colored Gel Slides (2 pieces)	Code: 0.26409.0000	
	Description: Selective filter 3000K - 2700K	Code: 0.26558.0000	
	Description: Selective filter 2700K - 2500K	Code: 0.26417.0000	
	Description: Selective filter 2700K - 2200K	Code: 0.26425.0000	
	Description: Selective filter 2700K - 2000K	Code: 0.26433.0000	
	Description: Selective filter 3000K - 3600K	Code: 0.26566.0000	
	Description: Selective filter 3000K - 4000K	Code: 0.26574.0000	
	Description: Dense texture honeycomb louvre	Code: 0.26441.0000	
	Description: Wide texture honeycomb louvre	Code: 0.26449.0000	
	Description: Elliptical beam lens	Code: 0.26492.0000	
	Description: Opal lens	Code: 0.26461.0000	
	Description: Spread lens	Code: 0.26469.0000	
	Description: Cross blade louvre	Code: 0.26480.0000	
	Description: Cone 45 ° wall washer	Code: 0.26496.00__	Finishes: 12 White 31 Black