


Project:	
Type:	
Description:	

YORI WALL 2.4"

INDOOR - RECESSED





Yori Wall 2.4"

Single and Double Emission



Version	Optics	ССТ	9W/5Wx2	Finishes
NF82 Single Emission 9W	B 12°Narrow	. <u>HW</u> 2700K	CRI >90 lm 1050/633 + 633	12 Embossed Matt White
PF82 Dual Emission 2X5W	E 20° Medum	HQ 3000 K	CRI >90 lm 1100/688 + 688	31 Embossed Matt Black
	H 32°Wide	WW 3000 K	CRI >80 lm 1300/810 + 810	C0¹ Royal Matt white
		WN ² 3500 K	CRI>80 lm 1330/855+855	B0¹ Royal Matt Black
		NN 4000 K	CRI>80 lm 1360/900+900	E0¹ Brushed Gold
		All lumens shown above are initial.		01¹ Chrome Plated
		Lumen delivered u	up to 1115/720+720lm	M0¹ Brushed Aluminium

Lumen maintenance: L80 B50=50,000h

- 1. Consult factory for lead time and pricing 2. For 3500K, must consult with factory to confirm availability

L0¹ Brushed Antique bronze

DRIVER Example: L.FLL66.0000 . F 0000

Dimming **Driver Location Driver Code Plate**

120/277V, 0-10V, dims down to 1%, 9W **V** 0-10V F Remote Driver (5+5)W LD18 powers 1 fixture at a time . 0000 No Plate

120/277V, Lutron EcoSystem Soft-9W on, Fade-to-Black, dims down to 1%, Lutron EcoSystem (5+5)W <u>LL66</u> powers 1 fixture at a time

NOTES

3. For emergency driver options, consult factory

Page 1 of 3



Project:	
Type:	
Description:	

YORI WALL 2.4" INDOOR - RECESSED

Technical Info

Driver:

Remote driver.

Optical features Light source features:

1 LED/3step/50,000 hrs Beam Angles: 12°, 20°, 32° **Physical features**:

Material: Die-cast aluminum

Mounting: Wall mounted ADA compliant

Surfaces: Wall Weight: 1.5 lbs

Maximum Remote Driver Distance:

60 Ft, 18Ga 80 Ft, 16Ga 100 Ft, 14 Ga

Luminaire Description:

Fixture Features: Yori Wall is a family of wall mounted luminaires that can naturally transform interiors and seamlessly blend in with the architecture. Yori Wall comes in three basic sizes, but its incredible flexibility really makes it stand out, along with the extensive range of high-end finishes, the interchangeable optics, and the direct and direct-indirect lighting versions.

Fixture Benefits: A wall mounted fixture with two versions: monoemission and bi-emission lighting. Special finishes: Royal matt white, Royal matt black, Brushed gold, Brushed bronze, Chrome plated, Brushed aluminum

Max Fixture Total Wattage:

9W LED: 12W 5W x2 LED: 13W

Accessories: Hollow cylinder dopped lens and optical accessories


Warranty: 5 Year LED.

ETL listed, Union assembled

Reggiani reserves the right to change details at any time. Rev 8/10/2021

TECHNICAL DRAWINGS

Yori Wall 2.4"



DRIVER

Large Remote Box



FOR USE WITH: LD18, LL66 Driver

- 1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.
- 2. Requires 3" clearance from any insulation



Project:	
Type:	
Description:	

YORI WALL 2.4" INDOOR - RECESSED

ACCESSORIES PRECISION

ACCESSORIES PRE	.0.5.011		
	Description: Precision - Narrow beam (12°)	Code: 0.35125.0000	
	Description: Precision - Medium beam (20°)	Code: 0.35126.0000	
	Description: Precision - Wide beam (32°)	Code: 0.35127.0000	
	Description: Glass filter 1 mm	Code: 0.26402.00	Finishes: 4A RED 5A Green 6A Blue 7A Pink 8A Yellow 9A orange
	Description: Colored Gel Slides (2 pieces)	Code: 0.26410.0000	
	Description: Selective filter 3000K - 2700K	Code: 0.26559.0000	
	Description: Selective filter 2700K - 2500K	Code: 0.26418.0000	
	Description: Selective filter 2700K - 2200K	Code: 0.26426.0000	
•	Description: Selective filter 2700K - 2000K	Code: 0.26434.0000	
	Description: Selective filter 3000K - 3600K	Code: 0.26567.0000	
	Description: Selective filter 3000K - 4000K	Code: 0.26575.0000	
	Description: Dense texture honeycomb louvre	Code: 0.26442.0000	
	Description: Wide texture honeycomb louvre	Code: 0.26450.0000	
	Description: Elliptical beam lens	Code: 0.26457.0000	
	Description: Opallens	Code: 0.26462.0000	
	Description: Spread lens	Code: 0.26470.0000	
	Description: Cross blade louvre	Code: 0.26477.0000	
©2.4° @2.4°	Description: Cylinder, hollow version (Ø 2.4", h 1.6")	Code: 0.26046.0000	