

Project:	
Type:	
Description:	

TRYBECA RECESSED DROP 1.5"

INDOOR - RECESSED



Round (Trim/Trimless)

Square (Trim/Trimless)



Round: ø1.9inch
Square: 1.9 x 1.9inch



5/8 inch Max Ceiling Thickness

LIGHT ENGINE

Example:



A.LH1AK.HW12

Shape

- L Round - Trim
- M Round - Trimless
- N Square - Trim
- P Square - Trimless

LED Wattage

- H1 AK 3W

CCT

<input type="radio"/> HW	2700 K	CRI >90	lm 266
<input type="radio"/> HQ	3000 K	CRI >90	lm 310
<input type="radio"/> WW	3000 K	CRI >80	lm 350
<input type="radio"/> WN ²	3500 K	CRI >80	lm 363
<input type="radio"/> NN	4000 K	CRI >80	lm 375

Finishes

- 12 Embossed Matt White
- 31 Embossed MattBlack

NOTES

- For alternate ceiling thickness consult factory
- For 3500K CCT, must consult with factory to confirm availability.

All lumens shown above are initial.
Lumen maintenance: L70 B10 = 50,000h

HOUSING/DRIVER (RETROFIT OPTION AVAILABLE, CONSULT FACTORY)

Example:



T.OSL18.049C

Dimming

- T Phase-Cut
- V 0-10V
- L Lutron EcoSystem

Housing/Driver Location

- O Open Housing with Remote Driver
- A IC/AT/CP Housing with Remote Driver

Driver Code

- SH15 120V; Phase Cut, dims down to 1%, powers 2-3 fixtures in series
- SL18 120V; Lutron 2-Wire Forward Phase, dims down to 1%, powers 2 fixtures in series
- SL11 120V; Lutron 2-Wire Forward Phase, dims down to 1%, powers 3 fixtures in series
- SZ19 120/277V; 0-10V, dims down to 1%, powers 1-5 fixtures in series
- SL121 120/277V; Lutron EcoSystem Soft-On, Fade-to-Black, dims down to 0.1%, powers 2-5 fixtures in series

Plate

- 049S Square Plate
- 049C Round Plate

NOTES

- for emergency driver options, consult factory,
- When powering multiple fixtures per driver, consult factory for additional components as required.

Project:	
Type:	
Description:	

TRYBECA RECESSED DROP 1.5"

INDOOR - RECESSED

Technical Info

Housing:

Remote driver is required and provided with an open housing for mounting.
Optional additional IC/AT/CP housing..

Optical features Light source features:

1 LED/3step/50,000 hrs

Physical features:

Material: Die-cast aluminum

Mounting: Recessed Mounting

Surfaces: Ceiling

Weight: 0.5 lbs

Maximum Driver Distance:

60 Ft, 18Ga

80 Ft, 16Ga

100Ft, 14 Ga

Luminaire Description:

Trim Features: Available dropped (1.2"), square or round.

Trim Benefits: Polycarbonate diffuser Nano Surface Treated for excellent LOR up to 87%. Internal reflector projects downlight while illuminating diffuser. Trim or trimless version. Requires remote Class 2 driver. Remote drivers can power multiple fixtures wired in series. Remote driver to be mounted in an accessible location. Above ceiling access required.

Max Fixture Total Wattage: 5W

Max Ceiling thickness: 5/8"

Warranty: 5 Year LED.

ETL listed, Union assembled


Reggiani reserves the right to change details at any time.

Rev 8/9/2021


Technical Drawings

LIGHT ENGINE


Round Trim




Square Trim



Round Trimless




Square Trimless




HOUSING/DRIVER

Open Housing Small



IC/AT/CP Housing Small




Small Remote Box




FOR USE WITH: SH15 Driver

Medium Remote Box



FOR USE WITH: SL121 Driver

Large Remote Box



FOR USE WITH: SL11, SL18 and SZ19 Driver

1. Requires 1/2" clearance from building members, 3" clearance from any insulation
2. Where no minimum install height indicated, minimum height is the trim height plus 1/2"
3. Hanger bars install on all 4 sides, expand from 13.5" to 24"
4. Hanger brackets accept FB bars, C-Channel, and 1/2" conduit for mounting
5. Non electrical housings allow fixture positioning for post ceiling installation.

1. Requires 1/2" clearance from building members
2. Hanger bars expand from 13.5" to 24", add 3.75" to the basic dimension of the housing
3. Hanger brackets accept FB bars, C-Channel, and 1/2" conduit for mounting

1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.
2. Requires 3" clearance from any insulation

1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.
2. Requires 3" clearance from any insulation

1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.
2. Requires 3" clearance from any insulation