

Project:	
Type:	
Description:	

TRYBECA RECESSED DROP 3" INDOOR - RECESSED



Round (Trim/Trimless)

Square (Trim/Trimless)



Round: ø3.3inch
Square: 3.3 x 3.3inch



1-1/4 inch Max Ceiling Thickness

LIGHT ENGINE Example:

A . □ □ □ . □ □ **A.LH1CK.HW12**

Shape	LED	Wattage	CCT	8W/9W DT	Finishes
<u>L</u> Round - Trim	<u>H1</u>	<u>CK</u> 8W	<u>HW</u> 2700K CRI >90 lm 900		<u>12</u> Embossed matt White
<u>M</u> Round - Trimless		<u>3K¹</u> 9W only for DT	<u>HQ</u> 3000K CRI >90 lm 936		<u>31</u> Embossed matt Black
<u>N</u> Square - Trim			<u>WW</u> 3000K CRI >80 lm 1104		
<u>P</u> Square - Trimless			<u>WN⁴</u> 3500K CRI >80 lm 1110		
			<u>NN</u> 4000K CRI >80 lm 1116		
			<u>DT¹</u> Warm Dim CRI >95 lm 105-1000		

NOTES
 1. Warm Dim only comes in 9W
 2. For alternate ceiling thickness consult factory
 3. Title 24 JA8 available; refer to last page for JA8 options
 4. For 3500K CCT, must consult with factory to confirm availability.

All lumens shown above are initial.
 Lumen maintenance: L80 B10 = 50,000h / L70 B10 = 50,000h for Warm-dim

HOUSING/DRIVER (RETROFIT OPTION AVAILABLE, CONSULT FACTORY) Example:

. □ □ □ . □ □ **V.ASD20.085S**

Dimming	Housing/Driver Location	Driver Code	Plate
<u>T</u> Phase-Cut	<u>O</u> Open Housing with Remote Driver	120V; Phase-Cut, dims down to 1%, powers 1 fixture at a time	<u>085S</u> Square Plate
	<u>A</u> IC/ AT/ CP Housing with Remote Driver	9W Open Version: <u>SH71</u> 120V; Phase-Cut, dims down to 1%, powers 1 fixture at a time 9W IC/AT/CP Version: <u>LH71</u>	<u>086C</u> Round Plate
<u>V</u> 0-10V		120/277V; 0-10V, dims down to 1%, powers 1 fixture at a time	
		9W Open Version: <u>SH74</u> 120/277V; 0-10, dims down to 1%, powers 1 fixture at a time 9W IC/AT/CP Version: <u>LH74</u>	
<u>L</u> Lutron EcoSystem		120/277V; Lutron EcoSystem Soft-on, Fade-to-Black, dims down to 1%, powers 1 fixture at a time	
		120/277V; Lutron EcoSystem Soft-on, Fade-to-Black, dims down to 1%, powers 1 fixture at a time	

NOTES
 5. For emergency driver options, consult factory

Project:	
Type:	
Description:	

TRYBECA RECESSED DROP 3"

INDOOR - RECESSED

Technical Info

Housing/Driver:

Remote driver is required and provided with an open housing for mounting.
Optional additional IC/AT/CP housing.

Optical features Light source features:

1 LED/3step/50,000 hrs

Physical features:

Material: Die-cast aluminum

Mounting: Recessed Mounting

Surfaces: Ceiling

Weight: 1.1 lbs

Maximum Driver Distance:

60 Ft, 18Ga

80 Ft, 16Ga

100Ft, 14 Ga

Luminaire Description:

Trim Features: Available dropped 2", square or round.

Trim Benefits: Polycarbonate diffuser Nano Surface Treated for excellent LOR up to 87%. Internal reflector projects downlight while illuminating diffuser. Trim or trimless version. Requires remote Class 2 driver. A single remote driver can power up to one fixture. Remote driver to be mounted in an accessible location. Above ceiling access required.

Max Fixture Total Wattage:

8W LED: 11W

9W DT LED: 12W

Max Ceiling thickness: 1-1/4"

Warranty: 5 Year LED





ETL listed, Union assembled

Reggiani reserves the right to change details at any time.

Rev 8/9/2021

Technical Drawings

LIGHT ENGINE




Project:	
Type:	
Description:	

TRYBECA RECESSED DROP 3"

INDOOR - RECESSED

HOUSING/ DRIVER


Open Housing Small



FOR USE WITH ALL WATTAGES

1. Requires 1/2" clearance from building members, 3" clearance from any insulation
2. Where no minimum install height indicated, minimum height is the trim height plus 1/2"
3. Hanger bars install on all 4 sides, expand from 13.5" to 24"
4. Hanger brackets accept FB bars, C-Channel, and 1/2" conduit for mounting
5. Non electrical housings allow fixture positioning for post ceiling installation.


IC/AT/CP Housing Small



FOR USE WITH: 8W

1. Requires 1/2" clearance from building members
2. Hanger bars expand from 13.5" to 24", add 3.75" to the basic dimension of the housing
3. Hanger brackets accept FB bars, C-Channel, and 1/2" conduit for mounting


IC/AT/CP Housing Large



FOR USE WITH: 9W

1. Requires 1/2" clearance from building members
2. Hanger bars expand from 13.5" to 24", add 3.75" to the basic dimension of the housing
3. Hanger brackets accept FB bars, C-Channel, and 1/2" conduit for mounting


Small Remote Box



FOR USE WITH: SH30 Driver

1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.
2. Requires 3" clearance from any insulation


Medium Remote Box



FOR USE WITH: SH71, LH71, SH74, and LH74 Drivers

1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.
2. Requires 3" clearance from any insulation

Large Remote Box



FOR USE WITH: SD20, SL97, SL66, LL66, SL30, and LL30 Drivers

1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.
2. Requires 3" clearance from any insulation

Project:	
Type:	
Description:	

TRYBECA RECESSED DROP 3" JA8 **INDOOR - RECESSED**

FOR JA8 FIXTURES, YOU MUST SPECIFY ONLY THE OPTIONS SHOWN BELOW



LIGHT ENGINE

Example:

J8 **H1** **A9** **DT** **J8.LH1A9.DT12**

Shape	LED	Wattage	CCT	Finishes
<ul style="list-style-type: none"> <u>L Round - Trim</u> <u>M Round - Trimless</u> <u>N Square - Trim</u> <u>P Square - Trimless</u> 	<u>H1</u>	<u>A9 9W</u>	<u>DT 1700K- 3000K CRI >95</u>	<ul style="list-style-type: none"> <u>12 Embossed Matt White</u> <u>31 Embossed Matt Black</u>

Lumen maintenance: L70B10=50,000h

HOUSING/DRIVER

Example:

A **T.ALH71.085S**

Dimming	Housing/Driver Location	Driver Code	Plate
<ul style="list-style-type: none"> <u>T Phase-Cut</u> <u>V 0-10V</u> <u>L Lutron EcoSystem</u> 	<ul style="list-style-type: none"> <u>A IC/ AT/ CP Housing with Remote Driver</u> 	<ul style="list-style-type: none"> <u>LH71 9W 120V; Phase-Cut, powers 1 fixture at a time, dims down to 1%</u> <u>LH74 9W 120/277V; 0-10V, powers 1 fixture at time, dims down to 1%.</u> <u>LL66 9W 120/277V; Lutron EcoSystem Soft-on, Fade-to-Black powers 1 fixture at a time, dims down to 1%</u> 	<ul style="list-style-type: none"> <u>085S Square plate</u> <u>086C Round plate</u>