

Project:	
Туре	
Description:	

YORI EVO BOX 3.7"

INDOOR - TRACK



Precision = Refractor Optics Performance = Reflector Optics

Yori Evo Box 3.7"

LIGHT ENGINE **COB LED Very Narrow Optic**

Example:

PH8

Finishes

12 Embossed matt white \$3 3 Circuit 120V

Embossed matt black

Finishes

31 Embossed matt black

JU Juno 2 Circuit 120V

G3 Global 3 Circuit 120V

Track

JU Juno 2 Circuit 120V G3 Global 3 Circuit 120V

12 Embossed matt white S3 3 Circuit 120V

T.PH84A.HW12.S3

Phase-Cut (1%) . PH8 Precision EcoSystem (0.1%) 0-10V (1%)

NOTES

availability

1. For 3500K, must consult with factory to confirm

2. Lutron EcoSystem Soft-on, Fade-to-black and 0-10V are

Optic Type Wattage 17W

Optics A 7° Precision

CCT 2700K CRI >90 lm 1870 . HW HQ 3000 K CRI > 90 lm 1920 ww 3000 K CRI > 80 lm 2320 WN³ 3500K CRI>80 lm 2360

NN 4000K CRI>80 lm 2400 HC 3000K CRI > 98 Im 1700

All lumens shown above are initial Lumen delivered up to 1512 lm Precision Lumen maintenance: L80 B10 = 50,000h

only offered with S3 track

COB LED Standard Optics

Example:

T.MH83E.HW12.JU

Dimming	Opt	ic Type	W	attage	0	ptics
T Phase-Cut (1%)	. MH8	Precision	3	12W	В	Precision 12°
L ² EcoSystem (0.1%)	MH9	Performance	4	17W	Ε	Precision 24°
V ² 0-10V (1%)			6	24W	В	Performance 10°
			8	33W	Ε	Performance 20°
			9	37W	Н	Performance 31°
					М	Performance 40°

CC.	Г		12W/17W/24W/33W/37W
. HW	2700 K	CRI >90	lm 1491/2067/2792/3635/3940
HQ	3000 K	CRI >90	lm 1533/2122/2860/3735/4000
ww	3000 K	CRI>80	lm 1859/2582/3487/4510/4880
WN¹	3500 K	CRI >80	lm 1890/2623/3545/4603/4985
NN	4000 K	CRI>80	lm 1920/2665/3602/4695/5090
нс	3000K	CRI >98	lm 1323/1834/2476/3142/3473

NOTES

1. For 3500K, must consult with factory to confirm

2. Lutron EcoSystem Soft-on, Fade-to-black and 0-10V are only offered with S3 track. Lutron EcoSvstem is only offered with 12W and 17W.

All lumens shown above are initial Lumen delivered up to 1690/2351/3170/4130/4477lm Precision Lumen delivered up to 1800/2500/3300/4110/4530Im Performance Lumen maintenance: L90 B10=50,000h

Warm Dimming COB LED

Example:

. MH8

8

В

DT

Finishes

T.MH88B.DT12.G3

Dimming Phase-Cut(1%) . MH8 Precision 8 33W B Precision 25° . DT V2 0-10V (1%)

Optic Type Wattage Optics

CCT 33W 1700-3000K CRI >95 lm 100-3100

12 Embossed matt white S3 3 Circuit 120V 31 Embossed matt black

JU Juno 2 Circuit 120V

G3 Global 3 Circuit 120V

Track

2. Lutron EcoSystem Soft-on, Fade-to-black and 0-10V are only offered with S3 track

Lumen delivered up to 1520 lm Lumen maintenance: L70 B10=50,000h All lumens shown above are initial



Project:	RFC
Туре	<u>ال</u>
Description:	Z
	 _

YORI EVO BOX 3.7"

INDOOR - TRACK

S33-CIRCUIT 120V TRACK

0.651

0.65111.0010

Track 0.651 S3 Track Length/Type

11 4ft. 3 circuit surface 120V 8 ft. 3 circuit surface 120V

4ft. 3 circuit recessed trim 120V 15 8 ft. 3 circuit recessed trim 120V

Finishes 0010 White

0021 Black



Surface



Recessed Trim

JU2-CIRCUIT120VTRACK

0.650

0.65034.0010

Track

Length/Type

0.650 Juno Track

33 2 ft. 2 circuit surface 120V 34 4 ft. 2 circuit surface 120V 35 6 ft. 2 circuit surface 120V 8 ft. 2 circuit surface 120V

Finishes

0010 White 0021 Black



Surface

NOTES

 $3. End \, cap \, is \, included \, with \, each \, section \, of \, track.$

G33-CIRCUIT 120V TRACK

0.720

0.72000.0010

0.720 Global Track

Length/Type 00 4 ft. 3 circuit surface 120V 8 ft. 3 circuit surface 120V

Finishes 0010 White 0021 Black



Surface

G3 RECESSED JACKET

0.720

0.72010.0021

Length/Type

 $\textbf{0.720}^{4} \ \mathsf{Global} \, \mathsf{Track} \quad \textbf{10} \quad \, 4 \, \mathsf{ft.} \, \mathsf{Recessed} \, \mathsf{trim} \, \mathsf{jacket} \, \mathsf{for} \, \mathsf{G3} \, \mathsf{track}$ 8 ft. Recessed trim jacket for G3 track **Finishes**

0010 White 0021 Black



Recessed Trim Jacket

 $4.\,G3\,surface\,track\,must\,be\,purchased\,with\,recessed\,jacket.$ See surface track above.

GENERAL NOTES FOR ALL TRACK TYPES

- · For tracks being configured in shapes, please consult factory.
- For additional mounting means or special ceiling accessories not shown on the following track accessory pages, please consult factory.
- · For additional track finishes, please consult factory.



Project:	
Туре	
Description:	

Technical Info

Optical features Light source features:

1 LED/3step/50,000 hrs

Beam angles:

Precision: 7°,12°,24°, 25°(only for warm-dim DT option)

Performance: 10°, 20°, 31°, 40°

Physical features:

Material: Die-cast aluminum

Mounting: Track

Adjustability: 356° horizontal axis, 90° vertical axis

Weight: 3.15 lbs

Luminaire Description:

FixtureFeatures: Yori Evo is the latest of the Yori family of projectors with many new features. Now Yori Evo comes with 4 sizes, from the 1.7" to the 3.7" for different levels of illumination and design aesthetics. The new optics let you decide the effect you prefer in terms of light output, beam angles and intensity. The range of accessories is another addition to the family and provides even moreflexibility to the Yori family.

Fixture Benefits: Part of the Yorifamily of lights assures consistent design. Ability to aim and quickly change beam spread. Available for multiple track formats.

Track Accessories: Please see following pages.

Max Fixture Total Wattage:

12W LED: 15W 17W LED: 20W 24W LED: 27W 33W LED: 36W

37W LED: 40W


Track Head Accessories: Wide range of Precision and Performance accessories available.

Warranty: 5 Year LED. ETL listed, Union assembled


Reggiani reserves the right to change details at any time.

Rev 8/10/2021

TECHNICAL DRAWINGS



S33-CIRCUIT 120V TRACK




JU2-CIRCUIT 120V TRACK


G33-CIRCUIT 120V TRACK


Surface Track

.49

Surface Track









Project:	KEG.
Туре	GIA
Description:	Ź

ACCESSORIES PRECISION

	Precision - Narrow beam (12°-12W, 17W, 24W, 33W, 37W) (25°-for warmdim only) Description: Precision - Medium beam (24°-12W,	Code: 0.35135.0000 Code: 0.35136.0000	
	17W, 24W, 33W, 37W) Description: Glass filter 1 mm	Code: 0.26406.00	Finishes: 4A RED 5A Green
			6A Blue 7A Pink 8A Yellow 9A orange
	Description: Colored Gel Slides (2 pieces)	Code: 0.26414.0000	
	Description: Selective filter 3000K - 2700K	Code: 0.26563.0000	
	Description: Selective filter 2700K - 2500K	Code: 0.26422.0000	
	Description: Selective filter 2700K - 2200K	Code: 0.26430.0000	
	Description: Selective filter 2700K - 2000K	Code: 0.26438.0000	
	Description: Selective filter 3000K - 3600K	Code: 0.26571.0000	
	Description: Selective filter 3000K - 4000K	Code: 0.26579.0000	
	Description: Dense texture honeycomb louvre	Code: 0.26446.0000	
	Description: Wide texture honeycomb louvre	Code: 0.26454.0000	
	Description: Elliptical beam lens	Code: 0.26459.0000	
	Description: Opallens	Code: 0.26466.0000	
	Description: Spread lens	Code: 0.26474.0000	
	Description: Cross blade louvre	Code: 0.26479.0000	
	Description: Barn doors	Code: 0.26487.0000	
8	Description: Cone 45 ° wall washer	Code: 0.26491.00	Finishes: 12 White 31 Black



Project:	돈
Туре	GIA
Description:	Ž

ACCESSORIES PERFORMANCE

	Description: Performance - Narrow beam (10°-12W, 17W, 24W, 33W, 37W)	Code: 0.35155.0000	
	Description: Performance - Medium beam (20°-12W, 17W, 24W, 33W, 37W)	Code: 0.35156.0000	
	Description: Performance - Wide beam (31°-12W, 17W, 24W, 33W, 37W)	Code: 0.35157.0000	
	Description: Performance - Wide beam (40°-12W, 17W, 24W, 33W, 37W)	Code: 0.35158.0000	
	Description: Glass filter 1 mm	Code: 0.26407.00	Finishes: 4A RED 5A Green 6A Blue 7A Pink 8A Yellow 9A orange
	Description: Colored Gel Slides (2 pieces)	Code: 0.26415.0000	
	Description: Selective filter 3000K - 2700K	Code: 0.26564.0000	
	Description: Selective filter 2700K - 2500K	Code: 0.26423.0000	
	Description: Selective filter 2700K - 2200K	Code: 0.26431.0000	
	Description: Selective filter 2700K - 2000K	Code: 0.26439.0000	
	Description: Selective filter 3000K - 3600K	Code: 0.26572.0000	
	Description: Selective filter 3000K - 4000K	Code: 0.26580.0000	
	Description: Dense texture honeycomb louvre	Code: 0.26447.0000	
	Description: Wide texture honeycomb louvre	Code: 0.26455.0000	
	Description: Elliptical beam lens	Code: 0.26495.0000	
	Description: Opal lens	Code: 0.26467.0000	
	Description: Spread lens	Code: 0.26475.0000	
	Description: Cross blade louvre	Code: 0.26483.0000	
8	Description: Cone 45 ° wall washer	Code: 0.26499.00	Finishes: 12 White 31 Black



Project:	N EG
Туре	
Description:	

S33-CIRCUIT 120V TRACK ACCESSORIES

	Description: Live End Feed Polarity Right	Code: 0.65117.00	Finishes: 10 White 21 Black
and the same of th	Description: Live End Feed Polarity Left	Code: 0.65118.00	Finishes: 10 White 21 Black
	Description: Live Straight Connector	Code: 0.65119.00	Finishes: 10 White 21 Black
	Description: L-Connector Polarity Internal	Code: 0.65121.00	Finishes: 10 White 21 Black
	Description: L-Connector Polarity External	Code: 0.65294.00	Finishes: 10 White 21 Black
	Description: T-Connector Polarity External Left	Code: 0.65123.00	Finishes: 10 White 21 Black
	Description: T-Connector Polarity External Right	Code: 0.65124.00	Finishes: 10 White 21 Black
	Description: T-Connector Polarity Internal Left	Code: 0.65125.00	Finishes: 10 White 21 Black
	Description: T-Connector Polarity Internal Right	Code: 0.65126.00	Finishes: 10 White 21 Black
X	Description: X-Connector	Code: 0.65127.00	Finishes: 10 White 21 Black
	Description: Surface Ceiling Clamp Three required for every eight feet and two required for every four feet.	Code: 0.65240.00	Finishes: 10 White 21 Black
	Description: T-Bar Ceiling Clamp Three required for every eight feet and two required for every four feet.	Code: 0.65233.00	Finishes: 10 White 21 Black
1,2774	Description: Dead End Cap for Surface/Pendant Track Includes locking screw.	Code: 0.65161.00	Finishes: 10 White 21 Black
Tree Land	Description: Dead End Cap for Recessed Track Includes locking screw.	Code: 0.65162.00	Finishes: 10 White 21 Black



Project:		REG
Туре		-GIAN
Description:		Z
		İĞH
	INDOOR - TRACK	ITING S.R.
		Ė

S33-CIRCUIT 120V TRACK ACCESSORIES

	Description:	Code:	Finishes:
	End Feed Cover for Recessed Track	0.65184.00	10 White 21 Black
	Description: Middle Feed Cover for Recessed Track	Code: 0.65185.00	Finishes: 10 White 21 Black
	Description: L-Connector Cover for Recessed Track	Code: 0.65186.00	Finishes: 10 White 21 Black
	Description: T-Connector Cover for Recessed Track	Code: 0.65187.00	Finishes: 10 White 21 Black
	Description: X-Connector Cover for Recessed Track	Code: 0.65188.00	Finishes: 10 White 21 Black
	Description: Stem Suspension Kit, End of Row Includes 3/8" IP stem, 5" diameter canopy, and metal mounting bracket for track at ends. Three suspension points required for every eight feet and two required for every four feet.	Code: Finishes: 10 White 21 Black	Length: 12 12" 18 18" 24 24" 48 48"
	Description: Stem Suspension Kit, Middle of Row Includes 3/8" IP stem, 5" diameter canopy, metal mounting bracket for track, and spline for joint. Three suspension points required for every eight feet and two required for every four feet.	Code: Finishes: 0.65428.0000 10 White 21 Black	Length: 12 12" 18 18" 24 24" 48 48"
	Description: Non-feed Aircraft Cable Suspension Kit, End of Row Includes aircraft cable, round head ceiling attachment, automatic cable gripper, and mounting bracket for track at ends. Three suspension points required for every eight feet and two required for every four feet.	Code: Finishes: 0.65205.000 10 White 21 Black	Length: 072 6' 108 9' 180 15'
-	Description: Non-feed Feed Aircraft Cable Susp. Kit, Middle of Row Includes aircraft cable, round head ceiling attachment, automatic cable gripper, and mounting bracket for track at joints. Three suspension points required for every eight feet and two required for every four feet.	Code: Finishes: 0.65429.000 10 White 21 Black	Length: 072 6' 108 9' 180 15'
	Pescription: Feed Aircraft Cable Suspension Kit, End of Row Includes aircraft cable, 5" diameter canopy, automatic cable gripper, and mounting bracket for track at ends. Three suspension points required for every eight feet and two required for every four feet.	Code: Finishes: 0.65426.000 10 White 21 Black	Length: 072 6' 108 9' 180 15'
	Description: Track Conductor Cutting Tool	Code: 0.65152.0000	Finishes: Not Painted
	Description: Surface mounting adapter for S3 track	Code: 0.65449.00	Finishes: 10 White 21 Black
	Description: 4' Cover Strip for track	Code: 0.65197.00	Finishes: 10 White 21 Black



Project:	REG
Туре	GIA
Description:	Z

JU 2 - CIRCUIT 120V TRACK ACCESSORIES

8	Description: Live Straight Connector Connects two track sections.	Code: 0.65038.00	Finishes: 10 White 21 Black
	Description: L-Connector Connects two track sections in a straight or L configuration. May be used as a feed point.	Code: 0.65040.00	Finishes: 10 White 21 Black
	Description: T-Connector Connects three track sections in a T configuration. Adjustable for right or left applications. May be used as a feed point.	Code: 0.65041.00	Finishes: 10 White 21 Black
	Description: X-Connector Connects four track sections in an X configuration. Factory wired for two separate 90° runs. May be field wired for one run. May be used as a feed point.	Code: 0.65043.00	Finishes: 10 White 21 Black
	Description: Live End Feed Direct wiring through a ceiling with end feed in suspension. Accepts 3/8" or 1/2" (trade size) electrical fittings. Top access.	Code: 0.65045.00	Finishes: 10 White 21 Black



Project:	REG
Туре	GIA
Description:	Z

G3 3 - CIRCUIT 120V TRACK ACCESSORIES

	Description: Live End Feed	Code: 0.72020.00	Finishes: 10 White 21 Black
	Description: Live Straight Connector	Code: 0.72022.00	Finishes: 10 White 21 Black
	Description: L-Connector	Code: 0.72023.00	Finishes: 10 White 21 Black
	Description: T-Connector Polarity Right	Code: 0.72024.00	Finishes: 10 White 21 Black
	Description: T-Connector Polarity Left	Code: 0.72025.00	Finishes: 10 White 21 Black
	Description: X-Connector	Code: 0.72026.00	Finishes: 10 White 21 Black
	Description: Dead End Cap	Code: 0.72029.00	Finishes: 10 White 21 Black
(O;	Description: Recessed Sleeve End Cap	Code: 0.72031.00	Finishes: Not Painted
110	Description: Bending Tool for Track Power Wires	Code: 0.72032.0000	Finishes: Not Painted
0	Description: Surface Ceiling Clamp Fast mounting "click" version. Three required for every eight feet and two required for every four feet.	Code: 0.72070.00	Finishes: 10 White 21 Black
	Description: T-Bar Ceiling Clamp Three required for every eight feet and two required for every four feet.	Code: 0.72071.00	Finishes: 10 White 21 Black
	Description: Recessed T-Bar Ceiling Clamp Three required for every eight feet and two required for every four feet.	Code: 0.72072.00	Finishes: 10 White 21 Black



Project:	REG
Туре	GIA
Description:	Z

G33-CIRCUIT 120V TRACK ACCESSORIES

	Description: Feed Stem Suspension Kit Includes 3/8" IP stem, 5" diameter canopy, and end feed suspension bracket. Three suspension points required for every eight feet and two required for every four feet.	Code: 0.65420.0000	Finishes: 10 White 21 Black	Length: 12 12" 18 18" 24 24" 36 36" 48 48"
	Description: Non-feed Stem Suspension Kit Includes 3/8" IP stem, 5" diameter canopy, and point suspension bracket. Three suspension points required for every eight feet and two required for every four feet.	Code: 0.65421.0000	Finishes: 10 White 21 Black	Length: 12 12" 18 18" 24 24" 36 36" 48 48"
5	Description: Aircraft Cable Suspension Kit Includes aircraft cable, ceiling mounting cup, and metal mounting bracket for track. Three suspension points required for every eight feet and two required for every four feet.	Code: 0.65422.000	Finishes: 10 White 21 Black	Length: 060 5' 108 9' 192 16'