

Project:	
Type:	
Description:	

## YORI PENDANT 1" INDOOR - PENDANT



Yori Pendant 16"      Yori Pendant 31.5"      Yori Pendant 63"



### LIGHT ENGINE Example:

**A** .    .   **A.LH50B.HW12**

#### Watt/Length

- . **LH50** 2W/16" long
- MH50** 2W/31.5" long
- NH50** 2W/63" long

#### Optics

- B** 9° Narrow
- E** 24° Medium
- H** 32° Wide

#### CCT

- . **HW** 2700K      CRI >90      140 lm
- HQ** 3000K      CRI >90      145 lm
- WW** 3000K      CRI >80      190 lm
- WN<sup>4</sup>** 3500K      CRI >80      195 lm
- NN** 4000K      CRI >80      200 lm

2W

#### Finishes

- 12** Embossed matt white
- 31** Embossed matt black
- CO<sup>1</sup>** Royal matt white
- B0<sup>1</sup>** Royal matt black
- NO<sup>1</sup>** Brushed copper
- DO<sup>1</sup>** Brushed brass
- EO<sup>1</sup>** Brushed gold
- O1<sup>1</sup>** Chrome
- M0<sup>1</sup>** Brushed aluminum
- LO<sup>1</sup>** Antiqued brushed bronze

All lumen above are initial.  
Lumen delivered up to 110lm.  
lumen maintainance L90B10=50,000h.

#### NOTES

1. Consult factory for lead time and pricing
2. 48" Standard cord length
3. For custom cord length, add .CXXX to the end of the ordering code, where XXX is the custom cord length in inches
4. For 3500K, must consult with factory to confirm availability
5. White canopy and cord are provided for all finishes above except for 31 and B0, unless black is requested at the time of order. Black canopy and cord are provided for 31 and B0

### DRIVER Example:

. **F**   . **0000** **T.FSH19.0000**

#### Dimming

#### Driver Location

#### Driver Code

#### Plate

**T** Phase-Cut      . **F** Remote Driver      2W **SH19** 120V; Phase-cut, dims down to 1%, powers 3-5 fixtures in series      . **0000** No plate

**V** 0-10V      2W **LD22** 120/277V; 0-10V, dims down to 1%, powers 1-5 fixtures in series

#### NOTES

6. For emergency driver options, consult factory

Project:	
Type:	
Description:	

## YORI PENDANT 1"

INDOOR - PENDANT

### Technical Info

**Driver:**

Remote driver.

**Mounting:**

Pendant. Mounts to standard octagon box using a canopy (ø5", 0.25" thick).

**Optical features Light source features:**

1 LED/3 step/50,000hrs  
Beam Angles: 9°, 24°, 32°

**Physical features :**

Material: Die-cast aluminum  
Weight: 16" version: .88 lbs; 31.5" version: 1.3 lbs; 63" version: 2.6 lbs  
Cable length: 48" Standard

**Max Remote Driver Distance:**

60 Ft , 18Ga  
80 Ft , 16Ga  
100 Ft , 14 Ga

**Luminaire Description:**

**Fixture Features:** LED and optics reside inside the cylinder concealing the light source.

**Fixture Benefits:** Part of the Yori family of recessed, track, surface, pendant, and wall. Allows design consistency.

**Max Fixture Total Wattage:** 3W

**Accessories:** Solid cylinder dropped lens accessories.


**Warranty:** 5 Year LED.

**ETL listed, Union assembled**


Reggiani reserves the right to change details at any time.  
Rev 8/10/2021

### TECHNICAL DRAWINGS


Yori Pendant 16"



Yori Pendant 31.5"



Yori Pendant 63"




### DRIVER

Small Remote Box



FOR USE WITH: SH19 Driver

Large Remote Box





FOR USE WITH: LD22 Driver

1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.
  2. Requires 3" clearance from any insulation
1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.
  2. Requires 3" clearance from any insulation

Project:	
Type:	
Description:	

**YORI PENDANT 1"** **INDOOR - PENDANT**

**ACCESSORIES**

	<p><b>Description</b> Cylinder, solid version (Ø 1", h 0.8")</p>	<p><b>Code</b> <b>0.26040.0000</b></p>
	<p><b>Description</b> Cylinder, solid version (Ø 1", h 3.1")</p>	<p><b>Code</b> <b>0.26041.0000</b></p>