


| | |
|--------------|--|
| Project: | |
| Type: | |
| Description: | |

YORI PENDANT 2.4"


INDOOR - PENDANT



Yori Pendant 8"



Yori Pendant 10"



Yori Pendant 24"



LIGHT ENGINE

COB LED Standard Optics

Example:

A .

.

A.RH51E.HW12

Watt/Length

- RH51** 5W / 8" long
- RH52** 9W / 10" long
- RH53** 12W / 24" long

Optics

- B** 12° Narrow
- E** 20° Medium
- H** 32° Wide

CCT

5W/9W/12W

- HW** 2700K CRI >90 lm 633/1050/1370
- HQ** 3000K CRI >90 lm 688/1100/1420
- WW** 3000K CRI >80 lm 810/1300/1700
- WN** 3500K CRI >80 lm 855/1330/1738
- NN** 4000K CRI >80 lm 900/1360/1775

Finishes

- 12** Embossed matt white
- 31** Embossed matt black
- CO** Royal matt white
- BO** Royal matt black
- NO** Brushed copper
- DO** Brushed brass
- EO** Brushed gold
- O1** Chrome
- MO** Brushed aluminum
- LO** Antiqued brushed bronze

NOTES

- Consult factory for lead time and pricing
- 48" Standard cord length
- For custom cord length, add .CXXX to the end of the ordering code, where XXX is the custom cord length in inches
- For 3500K, must consult with factory to confirm availability
- White canopy and cord are provided for all finishes above except for 31 and B0, unless black is requested at the time of order. Black canopy and cord are provided for 31 and B0

All lumens shown above are initial.
Lumens delivered up to 650/1000/1400 lm.
Lumen maintenance: L80 B10=50,000h.

Warm Dimming COB LED

Example:

A .

B

. **DT**

A.RH52B.DT31

Watt/Length

- RH52** 6W / 10" long
- RH53** 12W / 24" long

Optics

- B** 27° Medium

CCT

6W / 12W

- DT** 1700-3000K CRI >95 lm 100-550/105-1000

Finishes

- 12** Embossed matt white
- 31** Embossed matt black
- CO** Royal matt white
- BO** Royal matt black
- NO** Brushed copper
- DO** Brushed brass
- EO** Brushed gold
- O1** Chrome
- MO** Brushed aluminum
- LO** Antiqued brushed bronze

NOTES

- Consult factory for lead time and pricing
- 48" Standard cord length
- For custom cord length, add .CXXX to the end of the ordering code, where XXX is the custom cord length in inches
- White canopy and cord are provided for all finishes above except for 31 and B0, unless black is requested at the time of order. Black canopy and cord are provided for 31 and B0

All lumens shown above are initial.
Lumens delivered up to 350/690 lm
Lumen maintenance: L70 B50=50,000h.

| | |
|--------------|--|
| Project: | |
| Type: | |
| Description: | |

YORI PENDANT 2.4"

INDOOR - PENDANT

DRIVER

Example:

0000 **T.FMH70.0000**

| Dimming | Driver Location | Driver Code | Plate |
|--------------------|------------------------|--|----------------------|
| <u>T</u> Phase-Cut | <u>F</u> Remote Driver | 9W SH01 120V; Phase-cut, dims down to 1%, powers 1 fixture at a time | <u>0000</u> No plate |
| | | 9W LL05 120V; Lutron 2 Wire Forward Phase, dims down to 1%, powers 1 fixture at a time | |
| | | 12W MH70 120V; Phase-cut, dims down to 1%, powers 1 fixture at a time | |
| <u>V</u> 0-10V | | 5W LD120 120/277V; 0-10V, dims down to 1%, powers 1 fixture at a time | |
| | | 6W <i>Warm dim only</i> LD19 120/277V; 0-10V, dims down to 1%, powers 1 fixture at a time | |
| | | 9W MH74 120/277V; 0-10V, dims down to 1%, powers 1 fixture at a time | |
| | | 12W MH73 120/277V; 0-10V, dims down to 1%, powers 1 fixture at a time | |

NOTES
6. For emergency driver options, consult factory

| | |
|--------------|--|
| Project: | |
| Type: | |
| Description: | |

YORI PENDANT 2.4"

INDOOR - PENDANT

Technical Info

Driver:

Remote driver.

Mounting: Pendant. Mounts to standard octagon box using a canopy (ø5", 0.25" thick).

Optical features Light source features:

1 LED/3 step/50,000hrs

Beam Angles: 12°, 20°, 32°, 27° -DT warm dim only

Physical features :

Material: Die-cast aluminum

Weight: 8" version: 1.2 lbs; 10" version: 1.5 lbs; 24" version: 3.6 lbs

Cable Length: 48" Standard

Max Remote Driver Distance

60 Ft, 18Ga

80 Ft, 16Ga

100 Ft, 14 Ga

Luminaire Description:

Fixture Features: LED and optics reside inside the cylinder concealing the light source.

Fixture Benefits: Part of the Yori family of recessed, track, surface, pendant, and wall. Allows design consistency.

Max Fixture Total Wattage:

5W LED: 7W

6W LED: 9W

9W LED: 12W

12W LED: 15W

Accessories: Hollow cylinder dropped lens and optical accessories.

Warranty: 5 Year LED.


ETL listed, Union assembled

Reggiani reserves the right to change details at any time.


Rev 8/10/2021

TECHNICAL DRAWINGS


Yori Pendant 8"



Yori Pendant 10"




Yori Pendant 24"



DRIVER


Small Remote Box



FOR USE WITH: SH01 Driver

1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.
2. Requires 3" clearance from any insulation


Medium Remote Box



FOR USE WITH: MH70, MH73, and MH74 Drivers

1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.
2. Requires 3" clearance from any insulation

Large Remote Box



FOR USE WITH: LD120, LD19, and LL05 Drivers























1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.
2. Requires 3" clearance from any insulation

| | |
|--------------|--|
| Project: | |
| Type: | |
| Description: | |

YORI PENDANT 2.4"

INDOOR - PENDANT

ACCESSORIES

| | | | | |
|---|---|---|-------------------------------------|--|
|  |  | Description: Precision - Narrow beam (12°) (27°-For warm-dim only) | Code: 0.35125.0000 | |
|  |  | Description: Precision - Medium beam (20°) | Code: 0.35126.0000 | |
|  |  | Description: Precision - Wide beam (32°) | Code: 0.35127.0000 | |
|  | | Description: Glass filter 1 mm | Code: 0.26402.00__ | Finishes: 4A RED 5A Green 6A Blue 7A Pink 8A Yellow 9A orange |
|  | | Description: Colored Gel Slides (2 pieces) | Code: 0.26410.0000 | |
|  | | Description: Selective filter 3000K - 2700K | Code: 0.26559.0000 | |
|  | | Description: Selective filter 2700K - 2500K | Code: 0.26418.0000 | |
|  | | Description: Selective filter 2700K - 2200K | Code: 0.26426.0000 | |
|  | | Description: Selective filter 2700K - 2000K | Code: 0.26434.0000 | |
|  | | Description: Selective filter 3000K - 3600K | Code: 0.26567.0000 | |
|  | | Description: Selective filter 3000K - 4000K | Code: 0.26575.0000 | |
|  | | Description: Dense texture honeycomb louvre | Code: 0.26442.0000 | |
|  | | Description: Wide texture honeycomb louvre | Code: 0.26450.0000 | |
|  | | Description: Elliptical beam lens | Code: 0.26457.0000 | |
|  | | Description: Opal lens | Code: 0.26462.0000 | |
|  | | Description: Spread lens | Code: 0.26470.0000 | |
|  | | Description: Cross blade louvre | Code: 0.26477.0000 | |
|  |  | Description: Cylinder, hollow version (Ø2.4", h 1.6") | Code: 0.26046.0000 | |