

Project:	
Type:	
Description:	

YORI PENDANT 3.7"

INDOOR - PENDANT



Yori Pendant 10"

Yori Pendant 13"

Yori Pendant 16"

Yori Pendant 31.5"



LIGHT ENGINE

Example:

COB LED Standard Optics

A

A.VH53E.HQ12

Watt/Length

- VH53** 12W / 10" long
- VH54** 17W / 13" long
- VH56** 24W / 16" long
- ZH56** 24W / 31.5" long

Optics

- B** 12° Narrow
- E** 24° Medium
- H** 38° Wide
- M** 53° Very Wide

CCT

12W/17W/24W

HW	2700K	>90	lm 1491/2067/2792
HQ	3000K	>90	lm 1533/2122/2860
WW	3000K	>80	lm 1859/2582/3487
WN⁴	3500K	>80	lm 1890/2624/3544
NN	4000K	>80	lm 1920/2665/3602

Finishes

- 12** Embossed matt white
- 31** Embossed matt black
- CO¹** Royal matt white
- BO¹** Royal matt black
- NO¹** Brushed copper
- DO¹** Brushed brass
- EO¹** Brushed gold
- O1¹** Chrome
- MO¹** Brushed aluminum
- LO¹** Antiqued brushed bronze

NOTES

- Consult factory for lead time and pricing
- 48" Standard cord length
- For custom cord length, add .CXXX to the end of the ordering code, where XXX is the custom cord length in inches
- For 3500K, must consult with factory to confirm availability
- White canopy and cord are provided for all finishes above except for 31 and B0, unless black is requested at the time of order. Black canopy and cord are provided for 31 and B0

All lumens shown above are initial.
Lumens delivered up to 1500 lm/2100 lm/2800 lm
Lumen maintenance: L80 B10=50,000h

Warm Dimming COB LED

A

B

DT

Example:

A.VH56B.DT31

Watt/Length

- VH56** 25W / 16" long
- ZH56** 25W / 31.5" long

Optics

- B** 25° Medium

CCT

DT	1700K-3000K	>95	lm 100-2500
-----------	-------------	-----	-------------

Finishes

- 12** Embossed matt white
- 31** Embossed matt black
- CO¹** Royal matt white
- BO¹** Royal matt black
- NO¹** Brushed copper
- DO¹** Brushed brass
- EO¹** Brushed gold
- O1¹** Chrome
- MO¹** Brushed aluminum
- LO¹** Antiqued brushed bronze

NOTES

- Consult factory for lead time and pricing
- 48" Standard cord length
- For custom cord length, add .CXXX to the end of the ordering code, where XXX is the custom cord length in inches
- White canopy and cord are provided for all finishes above except for 31 and B0, unless black is requested at the time of order. Black canopy and cord are provided for 31 and B0

All lumens shown above are initial.
Lumens delivered up to 1200 lm
Lumen maintenance: L70/B50=50,000h

Project:	
Type:	
Description:	

YORI PENDANT 3.7" INDOOR - PENDANT

DRIVER Example: **V.FMH66.0000**

<input type="checkbox"/>	<input type="checkbox"/> F	<input type="checkbox"/>	<input type="checkbox"/> 0000	V.FMH66.0000
Dimming	Driver Location	Driver Code	Plate	
<u>T</u> Phase-Cut	<u>F</u> Remote Driver	12W <u>MH70</u> 120V; Phase-cut, dims down to 1%, powers 1 fixture at a time	<u>0000</u> No plate	
		12W <u>LL12</u> 120V; Lutron 2-Wire, Forward Phase, dims down to 1%, powers 1 fixture at a time		
		17W <u>MH62</u> 120V; Phase-cut, dims down to 1%, powers 1 fixture at a time		
		24/25W <u>MH60</u> 120V; Phase-cut, dims down to 1%, powers 1 fixture at a time		
<u>V</u> 0-10V		12W <u>MH73</u> 120/277V; 0-10V, dims down to 1%, powers 1 fixture at a time		
		17W <u>MH66</u> 120/277V; 0-10V, dims down to 1%, powers 1 fixture at a time		
		24/25W <u>MH64</u> 120/277V; 0-10V, dims down to 1%, powers 1 fixture at a time		
<u>L</u> Lutron EcoSystem		24/25W <u>LL74</u> 120/277V; Lutron EcoSystem Soft-On, Fade-to-Black, dims down to 1%, powers 1 fixture at a time		

NOTES
6. For emergency driver options, consult factory

Project:	
Type:	
Description:	

YORI PENDANT 3.7" INDOOR - PENDANT

Technical Info

Driver:

Remote driver.

Mounting: Pendant. Mounts to standard octagon box using a canopy (ø5", 0.25" thick).

Optical features Light source features:

1 LED/3 step/50,000 hrs

Beam Angles: 12°, 24°, 25° - DT only for warm dimming, 38°, 53°

Physical features:

Material: Die-cast aluminum

Weight: 10" version: 1.3 lbs; 13" version: 3.8 lbs; 16" version: 4.4 lbs;

31.5" version: 9.3 lbs

Cable length: 48" standard

Max Remote Driver Distance

60 Ft, 18Ga

80 Ft, 16Ga

100 Ft, 14 Ga

Luminaire Description:

Fixture Features: LED and optics reside inside the cylinder concealing the light source.

Fixture Benefits: Part of the Yori family of recessed, track, surface, pendant, and wall. Allows design consistency.

Max Fixture Total Wattage:

12W LED: 15W

17W LED: 20W

24W LED: 27W

25W LED: 28W

Accessories: Hollow cylinder dropped lens and optical accessories.

Warranty: 5 Year LED


ETL listed, Union assembled

Reggiani reserves the right to change details at any time.


Rev 8/10/2021

TECHNICAL DRAWINGS


Yori Pendant 10"




Yori Pendant 13"



Yori Pendant 16"




Yori Pendant 31.5"




DRIVER

Medium Remote Box



FOR USE WITH: MH70, MH73, MH62, MH66, MH60, MH64 Drivers

Large Remote Box



FOR USE WITH: LL12 and LL74 Drivers

1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.
2. Requires 3" clearance from any insulation

1. Must be installed in an accessible serviceable location with maximum 90 degrees Fahrenheit temperature.
2. Requires 3" clearance from any insulation

Project:	
Type:	
Description:	

YORI PENDANT 3.7"

INDOOR - PENDANT

ACCESSORIES

	Description: Precision - Narrow beam (12°) (25°-for warm-dim only)	Code: 0.35135.0000	
	Description: Precision - Medium beam (24°)	Code: 0.35136.0000	
	Description: Wide beam (38°)	Code: 0.35037.0000	
	Description: Very Wide beam (53°)	Code: 0.35038.0000	
	Description: Glass filter 1 mm	Code: 0.26406.00__	Finishes: 4A RED 5A Green 6A Blue 7A Pink 8A Yellow 9A orange
	Description: Colored Gel Slides (2 pieces)	Code: 0.26414.0000	
	Description: Selective filter 3000K - 2700K	Code: 0.26563.0000	
	Description: Selective filter 2700K - 2500K	Code: 0.26422.0000	
	Description: Selective filter 2700K - 2200K	Code: 0.26430.0000	
	Description: Selective filter 2700K - 2000K	Code: 0.26438.0000	
	Description: Selective filter 3000K - 3600K	Code: 0.26571.0000	
	Description: Selective filter 3000K - 4000K	Code: 0.26579.0000	
	Description: Dense texture honeycomb louvre	Code: 0.26446.0000	
	Description: Wide texture honeycomb louvre	Code: 0.26454.0000	
	Description: Elliptical beam lens	Code: 0.26459.0000	
	Description: Opal lens	Code: 0.26466.0000	
	Description: Spread lens	Code: 0.26474.0000	
	Description: Cross blade louvre	Code: 0.26479.0000	
	Description: Cylinder, hollow version (Ø 3.7" , h 2.4")	Code: 0.26047.0000	